



DeccoFloor

MICROTOP+

FLEXIBLE CONCRETE

SEAMLESS FLEXIBLE MICROTOPPING - SMOOTH FINISHED

Deccofloor Microtop+ is a one component coating formulated with cement, mineral fillers, correctors, ceramic and porcelain particles plus synthetic resins. Once mixed, a smooth troweled coating of extreme hardness and flexibility is obtained, characteristics that make it ideal to decorate floors, walls, interior areas, outdoor areas, residences, commercial buildings, objects, etc.

TARGETS

- ✓ Kitchen
- ✓ Bathrooms
- ✓ Living Rooms
- ✓ Bedrooms
- ✓ Countertops
- ✓ Walls
- ✓ Furnitures



High resistance to chemical abrasion
High mechanical resistance
Fast Dry
Waterproof
UV Stable



| TECHNICAL DATA | PRODUCT COMPOSITION |
|--|--|
| <p>Type: Microcement Monocomponent.</p> <p>appearance: White Powder</p> <p>Apparent density: Powder: 1.300 kg/m³.</p> <p>Solids content:100%</p> <p>Open time: 60 minutes. re-mix every 15 minutes.</p> <p>Maximum aggregate size: FINO: 0,1 mm GRUESO: 0,3 mm</p> <p>Mechanical Strength(EN 1015-11): Compression 28 días: ≥38N/mm². Fine Compression 28 días: ≥32N/mm². Thick/Base flexion 28 días: ≥ 10N/mm². Fine flexion 28 días: ≥ 8N/mm². Thick</p> <p>flexion 28 días: 10N/mm².</p> <p>Adhesion to concrete: 28 days: 1,75 N/mm².</p> <p>Application thickness: 1 mm per coat.</p> | <p>Microcement Mineral fillers</p> <p>Correction organic resins</p> <p>- Walls: add aprox. 22% of clean water - Floors: add aprox. 27% of clean water.</p> |

SURFACE PREPARATION: The surface should be clean and dry. For a property application, moisture the surface with Deccofloor Primer is recommended

PRE-APPLICATION: In a clean bucket pour the material and add water up to the 30%-35% ratio, mix the product with a low revolution driller (300-500 rpm) for at least 3 minutes, let stand for 10 minutes and then stir it again for 2 more minutes until getting a uniform mixture.

APPLICATION: Apply at least 2 coats of Deccofloor Microtop+ stirring it with a stain steel trowel (also a squeegee may be used). Let it dry and then sand very softly with a 220g/300g sand paper or similar, leave the surface flat. Apply Deccofloor Eco Seal uniformly.

COVERAGE: Up to 800 sq ft per coat (average). Coverage rates may vary depending on a surface porosity, texture, the application method and other local conditions.

PACKAGING: 44 lbs bucket/22 lbs bucket